

LED COLOUR

- 30 3000K
- 40 4000K

BEAM ANGLE

- 90 90°

FINISH

- W White

INCLUDED DRIVER

- FO Fixed Output

1.5W	Colour Temp (K)	3000	4000
	Luminous Flux @ 90° (lm)	91	99

Product Code

VIMA 2 / 1.5 / / / /

APPLICATIONS

Designed for use in retail, bars, shopping centres, public buildings, office and residential as an accent luminaire.

DESCRIPTION

The Vima 2 is a recessed wall light that produces a downward facing asymmetric wash of light.



This luminaire is available in a white finish and is manufactured complete with plug-and-play cable for easy installation.

FEATURES

- IP20
- Clean and neat design
- Uses SMD LED - low maintenance cost
- Dedicated thermal management
- No UV or IR emissions
- LED lifetime 50,000 hours
- Compatible with fixed output systems

NOTE

It is important that you check the compatibility of the dimmable units with the lighting controls supplier before placing your order.



1m	41.3 lx	1.1m ø
2m	10.3 lx	2.2m ø
3m	4.6 lx	3.3m ø
4m	1.9 lx	4.4m ø
5m	1.6 lx	5.5m ø

Parameter	Specification	
Light Source	SMD LED	
Power Consumption (W)	1.5	
LED Current (mA)	DC 350	
Operating Voltage (V)	AC 100-240V 50/60Hz	
Colour Temperature (K)	3000	4000
Luminous Flux @ 90° (lm)	91	99
CRI (Ra)	80	
Lifetime (Hrs)	50,000	
Ingress Protection (IP)	20	
Driver Options	Fixed Output	

