



LED COLOUR

- 30 3000K
- 40 4000K

BEAM ANGLE

- 90 90°

FINISH

- W White

INCLUDED DRIVER

- FO Fixed Output
- LT Leading & Trailing

15W	Colour Temp (K)	3000	4000
	Luminous Flux @ 90° (lm)	1220	1390

Product Code
 ASTERI 1 S / 15 / / / /

APPLICATIONS

The clean design of the Asteri range make them perfectly suited for installation in any setting, such as in retail, bars, shopping centres, public buildings, office and residential.

DESCRIPTION

The Asteri 1 S is a low-profile ceiling mounted square downlight that features an evenly distributed 90° beam angle and an opalised diffuser making this downlight suitable for a wide variety of architectural applications.



This luminaire is available in a white finish and is manufactured complete with plug-and-play cable for easy installation.

FEATURES

- IP20
- Clean and neat outlooking design
- Uses 4014 SMD LED - low maintenance cost
- Dedicated thermal management
- No UV or IR emissions
- LED lifetime 50,000 hours
- Compatible with fixed output and leading and trailing edge dimming systems

NOTE

It is important that you check the compatibility of the dimmable units with the lighting controls supplier before placing your order.



1m	452 lx	2.3m ø
2m	113 lx	4.7m ø
3m	50 lx	7.0m ø
4m	28 lx	9.4m ø
5m	18 lx	11.7m ø

Parameter		Specification	
Light Source		4014 SMD LED	
Power Consumption	(W)	15	
LED Current	(mA)	DC 350	
Operating Voltage	(V)	AC 100-240V 50/60Hz	
Colour Temperature	(K)	3000	4000
Luminous Flux @ 90°	(lm)	1220	1390
CRI	(Ra)	80	
Lifetime	(Hrs)	50,000	
Ingress Protection	(IP)	20	
Driver Options		Fixed Output, Leading & Trailing Edge Dimming	

