



LED COLOUR

- 27 2700K
- 30 3000K
- 40 4000K

BEAM ANGLE

- 15 15°
- 24 24°
- 38 38°
- 55 55°

FINISH

- W White
- B Black

DRIVER OPTION

- FO Fixed Output
- D DALI Dimming

Product Code

ROSSI 20/ 20 / / / /

| | | | | |
|------------|--------------------------|------|------|------|
| 20W | Colour Temp (K) | 2700 | 3000 | 4000 |
| | Luminous Flux @ 24° (lm) | 1390 | 1372 | 1379 |

APPLICATIONS

The contemporary Rossi track light range features an adjustable arm for the ultimate precision control and a high-efficiency light source offering up to 82 LL/CW ensuring a professional look with high visual comfort.





DESCRIPTION

The 55 mm diameter Rossi features a built-in flicker-free driver, a high-efficiency CRI90 light source, a choice of beam angles, a colour temperature option and an organised connecting system with die-cast aluminium housing for good heat dissipation.

The track-mounted adjustable arm allows for ultimate precision control with a 350° rotational arm and a 90° adjustable tilt.

Black or white finish as standard and compatible with a fixed output or DALI dimming system.

High efficiency and low power consumption makes the Rossi range environmentally friendly, helping significantly with carbon reduction programmes.



FEATURES

- IP20
- CRI90
- 82 LL/CW
- 350° rotational arm
- 90° adjustable tilt
- Precise light distribution
- Fixed output or DALI
- High efficiency
- Low power consumption
- No UV or IR emissions
- LED lifetime 50,000 hours

NOTE

It is important that you check the compatibility of the dimmable units with the lighting controls supplier before placing your order.

| Parameter | Specification | | |
|--------------------------------|--------------------|------|------|
| Light Source | Bridgelux | | |
| Power Consumption (W) | 20 | | |
| LED Current (mA) | 500 | | |
| Operating Voltage (V) | AC220-240V 50/60Hz | | |
| Colour Temperature (K) | 2700 | 3000 | 4000 |
| Luminous Flux up to @ 15° (lm) | 1430 | 1613 | 1168 |
| Luminous Flux up to @ 24° (lm) | 1390 | 1372 | 1379 |
| Luminous Flux up to @ 38° (lm) | 1323 | 1404 | 1650 |
| Luminous Flux up to @ 55° (lm) | 1604 | 1330 | 970 |
| Finish | Black, White | | |
| Mounting Type | Track | | |
| CRI (Ra) | 90 | | |
| Lifetime (Hrs) | 50000 | | |
| Dimensions (mm) | ø 55 x 170 x 235 | | |
| Ingress Protection (IP) | 20 | | |
| Operating Temperature (°C) | -25°C ~ 50°C | | |
| Driver Options | Fixed Output, DALI | | |

