



LED COLOUR

- 27 2700K
- 30 3000K
- 40 4000K

BEAM ANGLE

- 15 15°
- 24 24°
- 38 38°
- 55 55°

FINISH

- W White
- B Black

DRIVER OPTION

- FO Fixed Output

20W	Colour Temp (K)	2700	3000	4000
	Luminous Flux @ 24° (lm)	1390	1372	1379

Product Code

ROSSI 20 S/ 20 / / / /

APPLICATIONS

The contemporary Rossi range features an adjustable arm for the ultimate precision control and a high-efficiency light source offering up to 82 LL/CW ensuring a professional look with high visual comfort.





DESCRIPTION

The 55 mm diameter Rossi features a high-efficiency CRI90 light source, a choice of beam angles, a colour temperature option and an organised connecting system with die-cast aluminium housing for good heat dissipation.

The surface-mounted adjustable arm allows for ultimate precision control with a 350° rotational arm and a 90° adjustable tilt.

Black or white finish as standard and compatible with a fixed output system.

High efficiency and low power consumption makes the Rossi range environmentally friendly, helping significantly with carbon reduction programmes.



FEATURES

- IP20
- CRI90
- 82 LL/CW
- 350° rotational arm
- 90° adjustable tilt
- Precise light distribution
- Fixed output
- High efficiency
- Low power consumption
- No UV or IR emissions
- LED lifetime 50,000 hours

NOTE

It is important that you check the compatibility of the dimmable units with the lighting controls supplier before placing your order.

Parameter	Specification		
Light Source	Bridgelux		
Power Consumption (W)	20		
LED Current (mA)	500		
Operating Voltage (V)	AC220-240V 50/60Hz		
Colour Temperature (K)	2700	3000	4000
Luminous Flux up to @ 15° (lm)	1430	1613	1168
Luminous Flux up to @ 24° (lm)	1390	1372	1379
Luminous Flux up to @ 38° (lm)	1323	1404	1650
Luminous Flux up to @ 55° (lm)	1604	1330	970
Finish	Black, White		
Mounting Type	Surface		
CRI (Ra)	90		
Lifetime (Hrs)	50000		
Dimensions (mm)	ø 55 x 170 x 234		
Ingress Protection (IP)	20		
Operating Temperature (°C)	-25°C ~ 50°C		
Driver Options	Fixed Output		

